

ECO-LITE


Specialty Lighting Products

33 Rockland Park Ave, Tappan, NY 10983

Tel. 800-345-9652 Fax 845-365-9777

www.eco-lite.com

Product No. EL-JMGP202-LED



DIMENSIONS

HOUSING			HOUSING FRAME		TRIM		APERTURE		CUT-OUT	
L	W	H	L	W	L	W	L	W	L	W
A	B	C	D	E	F	G	H	I		
21-1/2"	5"	7-3/4"	18-1/4"	6-5/8"	13-1/4"	6-3/8"	11-1/4"	4-3/8"	12-3/4"	5-1/8"

DESCRIPTION

- New Construction 2-Light Linear recessed fixture comprised of separate housing and trim. Trim design allows use in ceilings up to 2" thick. No IC, must maintain 3" clearance from any insulation on all sides.

HOUSING:

3/4" overlap flanges combined with "pull-tight" torsion springs allows forgiveness in minor dry wall cutting errors.

MOUNTING:

Designed to be installed with overlap flange trim. Universal mounting brackets allow the use of conduit, HB or FB bar stock, or "C" channel bars. Consult factory for possible use in trimless "mud-in" installations.

AIMING:

Vertical: Inner Ring 40° - Outer Ring 45°

Rotation: 358°

LAMPING:

Use (2) PAR20, 120V 50W maximum per lamp. (Lamp not included).

LISTING:

UL & CUL Listed.


ECO-LITE

Specialty Lighting Products

33 Rockland Park Ave, Tappan, NY 10983
 Tel. 800-345-9652 Fax 845-365-9777
www.eco-lite.com

PAR 20 LED SPIRAL, Available in 3K, 4K, and 5K


Equivalent Source	
Standard	Up to 50W Halogen
L70 lumen depreciation design criteria = 50,000 hours	
Early Submission ENERGY STAR Life = 25,000 hours ²	
Housing	Painted
Socket	E26 Edison base (US) E27 (Europe)
Beam Spread	25°, 40°
Narrow Flood, Flood	
Operating Temperature	-20°C to +40°C
MOL	3.4", 86mm
Voltage	120 & 230 VAC
Weight	.33lbs., 150g
Power Factor	≥.90
Warranty	5 year limited
Standards	UL1993, File: E320663



ANNUAL OVERALL SAVINGS²

Standard Halogen

PAR20



² Savings based on 4,000 annual hours of operation, \$0.10 average cost per KWH. ³ \$40/hr. cost of labor and 15 minutes maintenance time to change lamp.

PAR20 Lifetime Savings: \$501

FEATURES

- Dimmable to 5% of light on most dimmers³
- Two unique beam distributions for application flexibility.
- Suitable for wet locations.
- 8 Watts – 84% more efficient than comparable 50 Watt Halogen lamps
- Maintenance free operation, lasts up to 16 times longer than conventional lighting.
- Superior thermal management allows for product usage in enclosed luminaires.
- Centralized optical package provides high quality point source beam versus pixilated designs.
- RoHS compliant – contains no mercury or lead.

DIMMER CAPABILITIES

Make	Model
Ace	34050, 3027596
Leviton	6633-PL, 6684, 6631, IPI06-1LX
Lutron	S-600PR-WH, DV-600PR-WH, TG-600PR-WH, AY600P, Q600P, GL600, CN-600PHW, DV-603PG, S-600, S-600P, LG-600P, D-600P, D-600PH, TT-300NLH, TG-603PGDVCL-153P, RRD-10ND, SZ-6ND, HW-RPM-4A-120, HxD-6ND, QSG-6P, LP-RPM-4A-120, PHPM-WBX
Legrand	DrRD4W